



# NovaSeal<sup>®</sup>

by Tuck

## NOVASEAL<sup>®</sup> PRO

### SYNTHETIC ROOF UNDERLAYMENT

NovaSeal<sup>®</sup> PRO is made from a completely waterproof construction of woven polypropylene and a slip resistant nonwoven top surface. PRO forms a barrier in your roofing system that helps protect residential steep slope roofs in the most extreme weather conditions. PRO synthetic roof underlayment delivers exceptional long-term weather barrier performance compared to traditional asphalt felt products.

PRO is designed for use under asphalt and synthetic shingles, metal in residential applications and primed cedar shakes.



One 10-square roll = five felt rolls!

### FEATURES & BENEFITS

#### COST REDUCTION

- Lightweight – shipping, staging, installing; significantly lighter than comparable asphalt felt products
- Requires fewer fasteners and fewer repairs than typical asphalt felt products

#### INSTALLER FRIENDLY

- Nonwoven walking surface provides superior slip resistant properties
- No special tools required
- Horizontal marker for overlap
- Lighter weight and easier to handle (10-square roll is only 18 lbs)

#### COVERS MORE

- Greater roof coverage per roll than traditional roofing felt

#### PROTECTION

- Extended UV protection – can be left exposed for up to 90 days
- Exceptional tear and puncture resistance



NovaSeal<sup>®</sup> PRO meets or exceeds all required building codes:

- ASTM D226 Types I & II, ASTM D4869



800-565-2000 | [tuckbuilding.com](https://tuckbuilding.com)



## PROPERTIES / TEST METHOD

Tensile Strength ASTM D5034	MD 100 lbs (45 kg) / CD 100 lbs (45 kg)
Tear Strength ASTM D4533	MD 25 lbs (11 kg) / CD 25 lbs (11 kg)
Liquid Water Transmission ASTM D4869	Pass
UV Exposure	90 Days
Permeability ASTM E96	< 0.05 Perms
Temperature Range	-40°F to 240°F / -40°C to 115°C
Limited Warranty	20 Years

## ROLL / PALLET SPECS

Length per Roll	250' / 76.2 m
Width per Roll	48" / 1.1 m
Weight per Roll	18 lbs / 8.1 kg
Roll Size	10 sq / 93 m <sup>2</sup>
Rolls per Pallet / Truck	64 / 2112



Scan for more info or visit [nova-seal.com](https://nova-seal.com)

