



A REGISTERED TRADEMARK OF INTERTAPE POLYMER INC. / UNE MARQUE DÉPOSÉE D'INTERTAPE POLYMER INC.

# 34200, 34300 & 34400 Series

## UTILITY PACKING TAPE



### DESCRIPTION

Biaxially-oriented polypropylene (BOPP) film, coated with pressure-sensitive emulsion acrylic adhesive. Best suited for reliable, all-temperature box sealing performance where resistance to aging, weathering, UV light, and yellowing are important. Provides excellent clarity, high shear strength to prevent 'flagging,' superior quick-stick performance, and controlled unwind to facilitate dispensing on manual or automatic case sealing machines.

### MAIN FEATURES

- Best suited for reliable, all-temperature box sealing performance
- Resistant to aging, weathering, UV light, and yellowing
- Excellent clarity
- High shear strength to prevent 'flagging'
- Controlled unwind to facilitate dispensing

### APPLICATIONS

- Light weight non-critical box sealing applications exposed to minimal shipping hazards and stress

### TECHNICAL DATA

Backing .....	0.91 mil	Cast BOPP Film
Adhesive.....		Emulsion Acrylic
Thickness.....	1.70 mil	
Adhesion to steel.....	11 oz/in	
Tensile strength .....	19 lb/in	
Elongation.....	100%	
Application Temperature.....	0°C (32°F) to 65°C (149°F)	
Operating Temperature Resistance.....	-35°C (-30°F) to 93°C (200°F)	

#### Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.