



A REGISTERED TRADEMARK OF INTERTAPE POLYMER INC. (P)
UNE MARQUE DÉPOSÉE D'INTERTAPE POLYMER INC.

34600 Series

PREMIUM SHIPPING TAPE



DESCRIPTION

Durable biaxially-oriented polypropylene (BOPP) film coated with high grade pressure-sensitive emulsion acrylic adhesive. Best suited for reliable, all-temperature box sealing performance where resistance to aging, weathering, UV light, and yellowing are important. Provides excellent clarity, high shear strength to prevent "flagging," superior quick-stick performance, and controlled unwind to facilitate dispensing on manual or automatic case sealing machines.

MAIN FEATURES

- Best suited for reliable, all-temperature box sealing performance
- Resistant to aging, weathering, UV light, and yellowing
- Excellent clarity
- High shear strength to prevent 'flagging'
- Controlled unwind to facilitate dispensing

APPLICATIONS

- Heavy weight box sealing and other packaging applications exposed to rougher shipping hazards and stress

TECHNICAL DATA

Backing	1.6 mil BOPP film
Adhesive.....	Emulsion Acrylic
Thickness.....	2.7 mil
Adhesion to steel.....	21 oz/in
Tensile strength.....	28 lb/in
Elongation.....	150%
Application Temperature.....	0°C (32°F) to 65°C (149°F)
Operating Temperature Resistance.....	-35°C (-30°F) to 93°C (200°F)

EXCELLENT CLARITY

ALL TEMPERATURE

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.